



LAVA 20 QUICK PRIMER

Safety Data Sheet

According to Regulation (EC) No. 1907/2006 (REACH) with its
Amendment Regulation (EC) No.1272/2008 (CLP) and EU 2020/878

Printing date 12.10.2021

Version number 5 (replaces version 4)

Revision: 12.10.2021

SECTION 1: Identification of the substance/mixture and of the company /undertaking

1.1 Product identifier

Trade name: LAVA 20 QUICK PRIMER

1.2 Relevant identified uses of the substance or mixture and uses advised against Professional use
Application of the substance / the mixture: Polyurethane primer

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

OWL WATERPROOFING SOLUTIONS

135 Slaney Road, Dublin Industrial Estate

Glasnevin, Dublin 11

Tel: +353 01 830 2250

Email: info@owlwaterproofing.co.uk

Website: www.owlwaterproofing.co.uk

1.4 Emergency telephone number:



European Emergency Tel.: +353 01 830 2250

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation EC No 1272/2008 CLP:



GHS02 flame

Flam. Liq. 3 H226 Flammable liquid and vapour.



GHS08 health hazard

Resp. Sens. 1 H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Carc. 2 H351 Suspected of causing cancer.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.



GHS07

Acute Tox. 4 H332 Harmful if inhaled.

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

STOT SE 3 H335 May cause respiratory irritation.

(Contd. on page 2)

Safety Data Sheet

According to Regulation (EC) No. 1907/2006 (REACH) with its Amendment Regulation (EC) No.1272/2008 (CLP) and EU 2020/878

Printing date 12.10.2021

Version number 5 (replaces version 4)

Revision: 12.10.2021

Trade name: LAVA 20 QUICK PRIMER

(Contd. of page 1)

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

2.2 Label elements**Labelling according to Regulation EC No 1272/2008 CLP:**

The product is classified and labelled according to the CLP regulation.

Hazard pictograms:

GHS02 GHS07 GHS08

Signal word: Danger**Hazard-determining components of labelling:**

Reaction mass of ethylbenzene and m-xylene and p-xylene
diphenylmethane diisocyanate, isomers and homologues
maleic anhydride
m-tolylidene diisocyanate

Addition reaction products of conjugated sunflower-oil fatty acids and tall-oil fatty acids with maleic anhydride

Hazard statements:

H226 Flammable liquid and vapour.

H332 Harmful if inhaled.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H317 May cause an allergic skin reaction.

H351 Suspected of causing cancer.

H335 May cause respiratory irritation.

H373 May cause damage to organs through prolonged or repeated exposure.

H304 May be fatal if swallowed and enters airways.

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P201 Obtain special instructions before use.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P260 Do not breathe dust/fume/gas/mist/vapours/spray.

P273 Avoid release to the environment.

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

P331 Do NOT induce vomiting.

P302+P352 IF ON SKIN: Wash with plenty of water and soap.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

(Contd. on page 3)

Safety Data Sheet

According to Regulation (EC) No. 1907/2006 (REACH) with its
Amendment Regulation (EC) No.1272/2008 (CLP) and EU 2020/878

Printing date 12.10.2021

Version number 5 (replaces version 4)

Revision: 12.10.2021

Trade name: LAVA 20 QUICK PRIMER

(Contd. of page 2)

P308+P313 IF exposed or concerned: Get medical advice/attention.
P403+P235 Store in a well-ventilated place. Keep cool.
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Additional information:

EUH204 Contains isocyanates. May produce an allergic reaction.

2.3 Other hazards**Results of PBT and vPvB assessment**

PBT: Not applicable.

vPvB: Not applicable.

SECTION 3: Composition/information on ingredients**3.2 Mixtures**

Description: Mixture: consisting of the following components.

Ingredients according Regulation (EU) 2020/878:

EC number: 905-562-9 Reg.nr.: 01-2119488216-32-XXXX	Reaction mass of ethylbenzene and m-xylene and p-xylene ⚠ Flam. Liq. 3, H226; ⚠ STOT RE 2, H373; Asp. Tox. 1, H304; ⚠ Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335; Aquatic Chronic 3, H412	25-50%
CAS: 9016-87-9	diphenylmethane diisocyanate, isomers and homologues ⚠ Resp. Sens. 1, H334; Carc. 2, H351; STOT RE 2, H373; ⚠ Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335, EUH204 Specific concentration limits: Eye Irrit. 2; H319: C ≥ 5 % Skin Irrit. 2; H315: C ≥ 5 % Resp. Sens. 1; H334: C ≥ 0.1 % STOT SE 3; H335: C ≥ 5 %	10-25%
CAS: 108-65-6 EINECS: 203-603-9 Index number: 607-195-00-7 Reg.nr.: 01-2119475791-29-XXXX	2-methoxy-1-methylethyl acetate ⚠ Flam. Liq. 3, H226	10-25%
CAS: 26471-62-5 EINECS: 247-722-4 Index number: 615-006-00-4 Reg.nr.: 01-2119454791-34-XXXX	m-tolyldiene diisocyanate ⚠ Acute Tox. 2, H330; ⚠ Resp. Sens. 1, H334; Carc. 2, H351; ⚠ Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335; Aquatic Chronic 3, H412, EUH204 Specific concentration limit: Resp. Sens. 1; H334: C ≥ 0.1 %	≥0.1-<1%

(Contd. on page 4)

Safety Data Sheet

According to Regulation (EC) No. 1907/2006 (REACH) with its Amendment Regulation (EC) No.1272/2008 (CLP) and EU 2020/878

Printing date 12.10.2021

Version number 5 (replaces version 4)

Revision: 12.10.2021

Trade name: LAVA 20 QUICK PRIMER

(Contd. of page 3)

EC number: 701-043-4 Reg.nr.: 01-2119976378-19-XXXX	Addition reaction products of conjugated sunflower-oil fatty acids and tall-oil fatty acids with maleic anhydride ⚠ Skin Irrit. 2, H315; Skin Sens. 1, H317	≥0.1-<1%
CAS: 108-31-6 EINECS: 203-571-6 Index number: 607-096-00-9 Reg.nr.: 01-2119472428-31-XXXX	maleic anhydride ⚠ Resp. Sens. 1, H334; STOT RE 1, H372; ⚠ Skin Corr. 1B, H314; ⚠ Acute Tox. 4, H302; Skin Sens. 1, H317 Specific concentration limit: Skin Sens. 1A; H317: C ≥ 0.001 %	≥0.001-<0.1%

SECTION 4: First aid measures

4.1 Description of first aid measures

General information:

Medical observation is required for at least 48 hours after the accident since symptoms of poisoning may not show up for several hours.

Ensure the first aider's personal safety.

Allow affected people to get some fresh air.

Request medical help immediately

After inhalation:

If the patient becomes unconscious, secure him in a side position for transportation.

Get fresh air & call a doctor immediately.

If symptoms last, see a doctor.

After skin contact:

Wash with soap and water immediately, then thoroughly rinse.

Seek emergency medical attention.

Take off any contaminated clothing.

After eye contact:

Rinse the opened eye under flowing water for 15 minutes.

Safeguard uninjured eye.

Consult a doctor if the symptoms continue.

After swallowing:

Do not force yourself to vomit; instead, contact emergency help right away.

Ensure you are getting lots of fresh air and drink. Make a doctor's appointment immediately.

Seek emergency medical attention.

4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing agents: CO2, powder or water spray. Use foam to put out major fires.

For safety reasons unsuitable extinguishing agents: Water with full jet

5.2 Special hazards arising from the substance or mixture No further relevant information available.

5.3 Advice for firefighters

Protective equipment:

Mouth respiratory protective device.

(Contd. on page 5)

Safety Data Sheet

According to Regulation (EC) No. 1907/2006 (REACH) with its Amendment Regulation (EC) No.1272/2008 (CLP) and EU 2020/878

Printing date 12.10.2021

Version number 5 (replaces version 4)

Revision: 12.10.2021

Trade name: LAVA 20 QUICK PRIMER

(Contd. of page 4)

Wear protective equipment.

Additional information

Collect contaminated fire fighting water separately. It must not enter the sewage system.

SECTION 6: Accidental release measures**6.1 Personal precautions, protective equipment and emergency procedures:**

Put on safety gear.

Avoid breathing in fumes.

Stay away from sources of ignition.

Avoid skin, eye and clothing contact.

6.1.1 For non-emergency personnel Make sure there is enough air circulation.**6.1.2 For emergency responders**

Wear safety gear when necessary. Keep vulnerable people at a distance.

Protective gear, gloves, goggles, and a breathing device with a type A filter are required for first-aid rescuers.

6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.**6.3 Methods and material for containment and cleaning up:**

Utilize absorbent material to collect (sand, diatomite).

Make sure there is enough airflow.

6.4 Reference to other sections:

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage**7.1 Precautions for safe handling** Make sure there is adequate exhaustion and ventilation at work.**Information about fire - and explosion protection:**

Avoid smoking and keep all combustible materials away.

Safeguard against electrostatic charges.

Store away from heat, fires, ignition, and direct sunlight.

7.2 Conditions for safe storage, including any incompatibilities**Storage:****Requirements to be met by storerooms and receptacles:**

Retain in a cold environment.

Store far from combustible materials

Receptacles should be ventilated.

Further information about storage conditions: Preserve the container tightly locked.**7.3 Specific end use(s)** No further relevant information available.

(Contd. on page 6)

Safety Data Sheet

According to Regulation (EC) No. 1907/2006 (REACH) with its
Amendment Regulation (EC) No.1272/2008 (CLP) and EU 2020/878

Printing date 12.10.2021

Version number 5 (replaces version 4)

Revision: 12.10.2021

Trade name: LAVA 20 QUICK PRIMER

(Contd. of page 5)

SECTION 8: Exposure controls/personal protection**8.1 Control parameters****Ingredients with limit values that require monitoring at the workplace:****CAS: 9016-87-9 diphenylmethane diisocyanate, isomeres and homologues**

WEL (Great Britain)	Short-term value: 0.07 mg/m ³
	Long-term value: 0.02 mg/m ³
	Sen; as -NCO

CAS: 108-65-6 2-methoxy-1-methylethyl acetate

WEL (Great Britain)	Short-term value: 548 mg/m ³ , 100 ppm
	Long-term value: 274 mg/m ³ , 50 ppm
	Sk
IOELV (EU)	Short-term value: 550 mg/m ³ , 100 ppm
	Long-term value: 275 mg/m ³ , 50 ppm
	Skin

CAS: 26471-62-5 m-tolyldiene diisocyanate

WEL (Great Britain)	Short-term value: 0.07 mg/m ³
	Long-term value: 0.02 mg/m ³
	Sen; as -NCO

CAS: 108-31-6 maleic anhydride

WEL (Great Britain)	Short-term value: 3 mg/m ³
	Long-term value: 1 mg/m ³
	Sen

DNELs

ETHYLBENZOLE REACTION MIXTURE, m-Xylol and p-Xylol.

DNEL Workers:

Inhalation - Intensive systemic effect = 289 mg / m³Inhalation - Chronic systemic effect = 77 mg / m³

Skin - Chronic systemic effect = 180 mg / kg

DNEL Consumers:

Mouth - Chronic systemic effect = 1.6 mg / kg

Inhalation - Intensive systemic effect = 174 mg / m³Inhalation - Chronic systemic effect = 14.8 mg / m³

Skin - Chronic systemic effect = 108 mg / kg

PNECs

ETHYLBENZOLE REACTION MIXTURE, m-Xylol and p-Xylol.

PNEC:

in fresh water 0.327 mg / l

in marine water 0,327 mg / l

for sediment in fresh water 12,46 mg / kg

for sediment in marinewater 12,46 mg / kg

for water, intermittent release of 0.327 mg / l

for STP 6,58 mg / l microorganisms

for the terrestrial area of 2,31 mg / kg

(Contd. on page 7)

Safety Data Sheet

According to Regulation (EC) No. 1907/2006 (REACH) with its Amendment Regulation (EC) No.1272/2008 (CLP) and EU 2020/878

Printing date 12.10.2021

Version number 5 (replaces version 4)

Revision: 12.10.2021

Trade name: LAVA 20 QUICK PRIMER

(Contd. of page 6)

8.2 Exposure controls

Individual protection measures, such as personal protective equipment

General protective and hygienic measures:

Avoid food, drink and feed.

Before breaks and after work, wash your hands.

Avoid eating, drinking and smoking while using the product.

Protective clothes should be stored separately.

Keep your hands away from your skin and eyes.

Respiratory protection:



In cases of inadequate ventilation, use an appropriate respiratory protection gear. Respiratory protection is necessary while spraying and in poorly ventilated work spaces. For brief durations of labor, a charcoal filter and particle filter A2-P2 (EN529) combination mask or an air-fed mask are advised.

Hand protection



Protective gloves resistant to chemicals (standard EN 374-1)

The material used for the gloves must be waterproof and resistant to the product, substance, or preparation. No advice for the glove material for the product, preparation, or chemical mixture can be made due to a lack of studies.

Choose the glove material while taking the degradation, diffusion, and penetration rates into account

Material of gloves

Hand protection when handling the product at room temperature:

Butyl rubber - IIR: thickness $\geq 0,5\text{mm}$; breakthrough time $\geq 480\text{min}$.

Fluorinated rubber - FKM: thickness $\geq 0,4\text{mm}$; breakthrough time $\geq 480\text{min}$.

Recommendation: contaminated gloves should be disposed of.

The selection of appropriate gloves is dependent not only on the materials, but also on additional quality indicators, and differs from manufacturer to manufacturer. The resilience of the glove material must thus be tested before use because the product is a blend of numerous components and cannot be predicted in advance.

Penetration time of glove material

The determined penetration times according to EN 16523-1:2015 are not performed under practical conditions. Therefore a maximum wearing time, which corresponds to 50% of the penetration time, is recommended.

Eye/face protection



Safety glasses with side-shields (frame goggles) (e.g. EN 166)

Body protection:



Chemically resistant, protective work clothing (EN 14605) and boots.

(Contd. on page 8)

Safety Data Sheet

According to Regulation (EC) No. 1907/2006 (REACH) with its
Amendment Regulation (EC) No.1272/2008 (CLP) and EU 2020/878

Printing date 12.10.2021

Version number 5 (replaces version 4)

Revision: 12.10.2021

Trade name: LAVA 20 QUICK PRIMER

(Contd. of page 7)

* SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

General Information

Physical state	Liquid
Colour:	transparent/yellowish
Odour:	Characteristic
Odour threshold:	Not determined
Melting point/freezing point:	Not determined
Boiling point or initial boiling point and boiling range	130 °C
Flammability	Not applicable
Lower and upper explosion limit	
Lower:	0.8 Vol %
Upper:	10.8 Vol %
Flash point:	27-32 °C (Reaction mass of ethylbenzene and m-xylene and p-xylene)
Auto-ignition temperature:	Product is not selfigniting.
Decomposition temperature:	Not determined
Viscosity:	
Kinematic viscosity	Not determined
Kinematic viscosity	
Dynamic at 20 °C:	<40 mPas
Solubility	
water:	Not miscible
Partition coefficient n-octanol/water (log value)	Not determined
Vapour pressure:	Not determined
Density and/or relative density	
Density at 20 °C:	1 g/cm ³
Relative density	Not determined
Vapour density	Not determined

9.2 Other information

Appearance:	VOC(g/l): 498
Form:	Liquid
Important information on protection of health and environment, and on safety.	
Auto-ignition temperature:	488 °C
Explosive properties:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
Solvent content:	
VOC (EC)	498 g/l
Cloud point / clarification point:	
Oxidising properties	Not considered as oxidising.
Evaporation rate	Not determined

Information with regard to physical hazard classes

Explosives	Void
Flammable gases	Void
Aerosols	Void
Oxidising gases	Void

(Contd. on page 9)

Safety Data Sheet

According to Regulation (EC) No. 1907/2006 (REACH) with its
Amendment Regulation (EC) No.1272/2008 (CLP) and EU 2020/878

Printing date 12.10.2021

Version number 5 (replaces version 4)

Revision: 12.10.2021

Trade name: LAVA 20 QUICK PRIMER

(Contd. of page 8)

Gases under pressure	Void
Flammable liquids	
Flammable liquid and vapour.	
Flammable solids	Void
Self-reactive substances and mixtures	Void
Pyrophoric liquids	Void
Pyrophoric solids	Void
Self-heating substances and mixtures	Void
Substances and mixtures, which emit flammable gases in contact with water	Void
Oxidising liquids	Void
Oxidising solids	Void
Organic peroxides	Void
Corrosive to metals	Void
Desensitised explosives	Void

SECTION 10: Stability and reactivity

10.1 Reactivity No further relevant information available.

10.2 Chemical stability

Thermal decomposition / conditions to be avoided Stable at environment temperature.

10.3 Possibility of hazardous reactions No dangerous reactions known.

10.4 Conditions to avoid Avoid heat, sparkles, naked flame or other sources of ignition.

10.5 Incompatible materials No further relevant information available.

10.6 Hazardous decomposition products No dangerous decomposition products known.

SECTION 11: Toxicological information**11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**

Acute toxicity Harmful if inhaled.

LD/LC50 values relevant for classification:

Inhalative	ATEmix (vapours)	17.7 mg/l (rat)
------------	------------------	-----------------

Reaction mass of ethylbenzene and m-xylene and p-xylene

Oral	LD50	4,300 mg/kg (rat)
Inhalative	LC50 (4h)	5,000 ppm (rat)
		5,000 ppm (rabbit)

CAS: 9016-87-9 diphenylmethane diisocyanate, isomeres and homologues

Oral	LD50	>10,000 mg/kg (rat)
Dermal	LD50	>10,000 mg/kg (rabbit)
Inhalative	LC50/4 h (vapour)	0.493 mg/l (rat) (OECD 401)
		0.493 mg/l (rabbit)

CAS: 108-65-6 2-methoxy-1-methylethyl acetate

Oral	LD50	>5,000 mg/kg (rat)
Dermal	LD50	>5,000 mg/kg (rat)

(Contd. on page 10)

Safety Data Sheet

According to Regulation (EC) No. 1907/2006 (REACH) with its
Amendment Regulation (EC) No.1272/2008 (CLP) and EU 2020/878

Printing date 12.10.2021

Version number 5 (replaces version 4)

Revision: 12.10.2021

Trade name: LAVA 20 QUICK PRIMER

(Contd. of page 9)

Inhalative	LC50 (4h)	1,805.05 ppm (rat)
CAS: 1330-20-7 Xylene mixture of isomers		
Oral	LD50	4,300 mg/kg (rat)
Dermal	LD50	1,700 mg/kg (rabbit)
Inhalative	LC50 (4h)	5,000 ppm (rat)
CAS: 26471-62-5 m-tolyldene diisocyanate		
Oral	LD50	4,130 mg/kg (rat)
Dermal	LD50	>9,400 mg/kg (rabbit)
CAS: 108-31-6 maleic anhydride		
Oral	LD50	400 mg/kg (rat)
Dermal	LD50	2,620 mg/kg (rabbit)

Skin corrosion/irritation Causes skin irritation.

Serious eye damage/irritation Causes serious eye irritation.

Respiratory or skin sensitisation

Inhalation may result in symptoms of allergies, asthma, or breathing problems.

Might result in an allergic skin condition.

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity

Carcinogen, Category 2

Cancer-causing agent suspected

Reproductive toxicity Based on available data, the classification criteria are not met.

STOT-single exposure

The product is classified as Specific Target Organ Toxicity after single exposure Category 3

May cause respiratory irritation.

STOT-repeated exposure

STOT Repeated Exposure Category 2

May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard

The product is classified Aspiration toxicity Category 1

May be fatal if swallowed and enters airways.

Additional toxicological information:

Sensitisation Sensitization possible through skin contact

CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)**CAS: 108-65-6 2-methoxy-1-methylethyl acetate**

NOEC (28d) | 1.659 mg/l (crustacean)

Carc. 2

11.2 Information on other hazards**Endocrine disrupting properties**

None of the ingredients is listed.

(Contd. on page 11)

Safety Data Sheet

According to Regulation (EC) No. 1907/2006 (REACH) with its
Amendment Regulation (EC) No.1272/2008 (CLP) and EU 2020/878

Printing date 12.10.2021

Version number 5 (replaces version 4)

Revision: 12.10.2021

Trade name: LAVA 20 QUICK PRIMER

(Contd. of page 10)

SECTION 12: Ecological information**12.1 Toxicity****Aquatic toxicity:****CAS: 108-65-6 2-methoxy-1-methylethyl acetate**

EC50 (48h) 8.8 mg/l (crustacean)

LC50 (96h) 6.83 mg/l (fis)

CAS: 1330-20-7 Xylene mixture of isomers

EC50 (48h) >7.4 mg/l (daphnia magna)

LC50 (96h) 2.6 mg/l (fis)

NOEC r (72h) 440 mg/l (algae)

CAS: 26471-62-5 m-tolylidene diisocyanate

EC50 (48h) 12.5 mg/l (daphnia magna)

LC50 (96h) 133 mg/l (Oncorhynchus mykiss)

12.2 Persistence and degradability No further relevant information available.**12.3 Bioaccumulative potential** No further relevant information available.**12.4 Mobility in soil** No further relevant information available.**12.5 Results of PBT and vPvB assessment****PBT:** Not applicable.**vPvB:** Not applicable.**12.6 Endocrine disrupting properties** For information on endocrine disrupting properties see section 11.**12.7 Other adverse effects****Remark:** Harmful to fish**Additional ecological information:****General notes:**

Environmentally hazardous components are present in the product.

Detrimental to aquatic life.

SECTION 13: Disposal considerations**13.1 Waste treatment methods****Recommendation**

Dispose according to National Regulations.



Not to be disposed of with regular trash. Do not let product enter the drainage system.

Contact manufacturer for recycling information.

Uncleaned packaging:**Recommendation:**

Official guidelines must be followed while disposing of materials.

(Contd. on page 12)

Safety Data Sheet

According to Regulation (EC) No. 1907/2006 (REACH) with its Amendment Regulation (EC) No.1272/2008 (CLP) and EU 2020/878

Printing date 12.10.2021

Version number 5 (replaces version 4)

Revision: 12.10.2021

Trade name: LAVA 20 QUICK PRIMER

After cleaning, packaging can be recycled or used again.

(Contd. of page 11)

SECTION 14: Transport information

14.1 UN number or ID number
ADR, IMDG, IATA

UN1866

14.2 UN proper shipping name
ADR
IMDG, IATA

1866 RESIN SOLUTION
RESIN SOLUTION

14.3 Transport hazard class(es)
ADR, IMDG, IATA



Class
Label

3 Flammable liquids.
3

14.4 Packing group
ADR, IMDG, IATA

III

14.5 Environmental hazards:
Marine pollutant:

No

14.6 Special precautions for user
Hazard identification number (Kemler code):
EMS Number:
Stowage Category

Warning: Flammable liquids.
30
F-E,S-E
A

14.7 Maritime transport in bulk according to IMO instruments

Not applicable.

Transport/Additional information:

ADR
Limited quantities (LQ)
Excepted quantities (EQ)

5L
Code: E1
Maximum net quantity per inner packaging: 30 ml
Maximum net quantity per outer packaging: 1000 ml

Transport category
Tunnel restriction code

3
D/E

IMDG
Limited quantities (LQ)
Excepted quantities (EQ)

5L
Code: E1
Maximum net quantity per inner packaging: 30 ml
Maximum net quantity per outer packaging: 1000 ml

(Contd. on page 13)

Safety Data Sheet

According to Regulation (EC) No. 1907/2006 (REACH) with its Amendment Regulation (EC) No.1272/2008 (CLP) and EU 2020/878

Printing date 12.10.2021

Version number 5 (replaces version 4)

Revision: 12.10.2021

Trade name: LAVA 20 QUICK PRIMER

(Contd. of page 12)

UN "Model Regulation":

UN 1866 RESIN SOLUTION, 3, III

SECTION 15: Regulatory information**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

Directive 94/62/EC on packaging and packaging waste.

REACH Regulation 1907/2006/EC

Regulation (EU) 2020/878

CLP Regulation 1272/2008/EC

Directive 98/24/EC on safeguarding employees' health and safety against hazards posed by chemical agents at work.

Youth protection at work: amended version of Council Directive 94/33/EC.

The amended version of Directive 92/85/EEC on the adoption of measures to promote advancements in the safety and health at work of pregnant employees, new mothers, and nursing employees

Directive 2012/18/EU

Named dangerous substances - ANNEX I Substance is not listed.

Seveso category P5c FLAMMABLE LIQUIDS

Qualifying quantity (tonnes) for the application of lower-tier requirements 5.000 t

Qualifying quantity (tonnes) for the application of upper-tier requirements 50.000 t

REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3, 74

National regulations:**Other regulations, limitations and prohibitive regulations****Substances of very high concern (SVHC) according to REACH, Article 57**

It doesn't contain substances of very high concern (SVHC).

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on what we know right now. This, however, does not create a legally binding business relationship or a guarantee for any particular product characteristics.

Relevant phrases

H226 Flammable liquid and vapour.

H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin.

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H330 Fatal if inhaled.

H332 Harmful if inhaled.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H335 May cause respiratory irritation.

H351 Suspected of causing cancer.

H372 Causes damage to organs through prolonged or repeated exposure.

(Contd. on page 14)

Safety Data Sheet

According to Regulation (EC) No. 1907/2006 (REACH) with its Amendment Regulation (EC) No. 1272/2008 (CLP) and EU 2020/878

Printing date 12.10.2021

Version number 5 (replaces version 4)

Revision: 12.10.2021

Trade name: LAVA 20 QUICK PRIMER

(Contd. of page 13)

H373 May cause damage to organs through prolonged or repeated exposure.

H412 Harmful to aquatic life with long lasting effects.

EUH204 Contains isocyanates. May produce an allergic reaction.

Department issuing SDS:**OWL WATERPROOFING SOLUTIONS**

135 Slaney Road, Dublin Industrial Estate

Glasnevin, Dublin 11

Tel: +353 01 830 2250

Email: info@owlwaterproofing.co.ukWebsite: www.owlwaterproofing.co.uk**Version number of previous version: 4****Abbreviations and acronyms:**

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

SVHC: Substances of Very High Concern

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 3: Flammable liquids – Category 3

Acute Tox. 4: Acute toxicity – Category 4

Acute Tox. 2: Acute toxicity – Category 2

Skin Corr. 1B: Skin corrosion/irritation – Category 1B

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Resp. Sens. 1: Respiratory sensitisation – Category 1

Skin Sens. 1: Skin sensitisation – Category 1

Carc. 2: Carcinogenicity – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

Asp. Tox. 1: Aspiration hazard – Category 1

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

*** Data compared to the previous version altered.**